



Safety Data Sheet

SDS ID: Stock Code TTC

Revision date: May 6, 2015

Section 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Whitlam All Purpose Clear Siliconized Acrylic Caulk

Synonyms: None

Chemical family: N/A

Producer: J.C. Whitlam Manufacturing Company
200 West Walnut Street
P.O. Box 380
Wadsworth, Ohio 44282-0380
www.icwhitlam.com

Telephone: 330-334-2524 Available during normal business hours

Emergency: 330-334-2524 Available during normal business hours

Section 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Harmful if swallowed or absorbed through skin.

Precautionary Statements: May cause eye, skin, nose, throat and respiratory tract irritation.

Inhalation: Material is not likely to present an inhalation hazard at ambient conditions.

Ingestion: Do not induce vomiting.

Skin contact: May cause irritation.

Eye contact: Direct contact may cause mild irritation.

Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

Material information:

Name	CAS No.	Weight %
Acrylic Emulsion (mixture)	-	<95
Petroleum Distillate	64742-48-9	<1
Ammonium Hydroxide	7664-41-7	<0.5
Non-Hazardous Ingredients*	-	<2

Note: The above weight percentages are represented in ranges as estimates. Due to variation among production batches, component percentages may vary.

*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 2910.1200).

Section 4. FIRST AID MEASURES

- Inhalation:** Remove to fresh air. If breathing is difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.
- Skin contact:** Wash with soap and water for at least 15 minutes. Get medical attention if symptoms persist. Remove and wash contaminated clothing.
- Ingestion:** DO NOT INDUCE VOMITING. Get immediate medical attention.
- Eye contact:** Immediately flush with large quantities of water for at least 15 minutes until irrigation subsides. Get medical attention.

Section 5. FIREFIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide, dry chemical or foam water fog

Specific hazards: None known

Special protective equipment for firefighters: Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

	NFPA rating:	HMIS rating:	
Health:	1	N/A	
Flammability:	1	N/A	
Instability/reactivity:	0	N/A	
Other:	N/A	N/A	

Section 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Wear proper protective equipment (Section 8).
Large Spill:	No data available.
Methods for Containment and Clean up	Use absorbent material or scrape up dried material and place in approved container.

Section 7. HANDLING AND STORAGE

Handling:	Keep out of reach of children and pets. Do not take internally. Do not breathe vapors. Use only with adequate ventilation. Wash thoroughly after handling. Avoid contact with eyes, skin & clothing. Open windows & doors to ensure cross ventilation and fresh air during application and curing.
Storage:	Close container after each use. Store containers away from excessive heat and freezing. Do not store at temperatures above 120°F. Store away from caustics & oxidizers

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Name	CAS No.	ACGIH® TLV® Exposure Limits:	Federal OSHA PELs	OSHA PELs 1989 ^C
Acrylic Emulsion (mixture)		Not established	NA	Not established
Petroleum Distillate	64742-48-9	100 ppm	NA	100 ppm
Ammonium Hydroxide	7664-41-7	25 ppm	NA	50 ppm
Non-Hazardous Ingredients*		NA	NA	

*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 2910.1200).

PERSONAL PROTECTIVE EQUIPMENT

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator with organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits.

Skin and body protection: Rubber gloves. Other protective equipment not required under normal use.

Eye protection: Goggles or safety glasses with side shields.

Hygiene measures: Remove and wash contaminated clothing before re-use. Wash hands before breaks and at end of workday.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear Paste
Physical state (solid/liquid/gas):	Solid
Substance type (pure/mixture):	Mixture
Color:	Clear
Odor:	Mild acrylic / ammonia
Molecular weight:	Not Available
pH:	7 to 9
Boiling point/range (5-95%):	210°F to 220°F (99°C -104°C)
Melting point/range:	Not Available
Decomposition temperature:	Not Available
Specific gravity:	Approximately 1.03 to 1.08
Vapor density:	>1(AIR = 1) Heavier than air
Vapor pressure:	Not established
Evaporation rate (Butyl acetate= 1):	<1
Flash point, method used:	>200°F (93°C) Seta Closed Cup
Water solubility:	Slight, before cure
VOC Content:	<0.5%/wt, <10 g/L
Auto-ignition temperature:	Not Established
Flammable limits in air — lower (%):	Not Established
Flammable limits in air — upper (%):	Not Established

Section 10. STABILITY AND REACTIVITY

Reactivity:	No data available
Stability:	Stable under normal conditions.
Possibly hazardous reactions:	No data available
Conditions to avoid:	Excessive heat and freezing.
Incompatible Materials:	Incompatible with strong bases and oxidizing agents.
Hazardous decomposition products:	Normal decomposition products, i.e., CO ₂ , NO ₂
Polymerization:	Will not occur.

Section 11. TOXICOLOGICAL INFORMATION

ACGIH: Small amounts of Silica, crystalline present in Calcium Carbonate and trace residual Formaldehyde present in base emulsion are suspected human carcinogens.

OSHA: Trace residual Formaldehyde present in base emulsion viewed as a possible cancer hazard.

IARC: Trace residual Formaldehyde: Human carcinogen.

NTP: Silica, crystalline, present in small amount in Calcium Carbonate Filler: Known carcinogen. Trace residual Formaldehyde: Anticipated carcinogen.

DATA WITH POSSIBLE RELEVANCE TO HUMANS: Product contains trace amounts of residual Formaldehyde. OSHA & NTP identify Formaldehyde as a potential carcinogen. IARC identifies Formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, with human significance unknown. Rats have shown carcinogenic effects in respiratory system. Risk should be minimal when used w/ adequate ventilation. Maintain adequate ventilation to prevent exposure above OSHA exposure limits.

Section 12. ECOLOGICAL INFORMATION

Ecotoxicity effects: Not known or expected under normal use.

Persistence None

Degradability: None

Section 13. DISPOSAL CONSIDERATIONS

Cleanup considerations: Dispose of in accordance with Federal, State and Local regulations.

Section 14. TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION: Shipping information applicable for domestic ground transport only. Different categorization may be necessary if shipped via other modes of transportation and/or to non-domestic destinations. PRODUCT NOT REGULATED BY DOT

Section 15. REGULATORY INFORMATION

CERCLA – SARA HAZARD CATEGORY: Immediate health hazard; chronic health hazard.
U.S. STATE REGS: See Section 16.

SARA 313: None.

TSCA: All ingredients either on TSCA Inventory or exempt.

Section 16. OTHER INFORMATION

Standards and Certification Listings:

NJ Right-to-Know: (Top 5 Ingredients): Calcium Carbonate (1317-65-3), Base Acrylic Emulsion (mixture), Benzoate Ester (proprietary), Water (7732-18-5), Petroleum Distillate (64742-48-9).

Pennsylvania Right-to-Know (Non-Haz @ >3%): Water (7732-18-5).

Ingredients Known to State of California to cause cancer and/or developmental toxicity and/or reproductive toxicity: Formaldehyde (50-00-0), Silica, crystalline (14808-60-7).

Titanium Dioxide (13463-67-7) added to Massachusetts Right-to-Know List, Minnesota Hazardous Substance List, New Jersey Right-to-Know List, Pennsylvania Right-to-Know List and Rhode Island Hazardous Substance list.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Non-white colors may contain carbon black in color dispersions.

The information and recommendations contained herein are based upon tests, data, and information resources believed to be reliable. However, the J.C. Whitlam Manufacturing Company, Inc., and its related operations or divisions (Whitlam) do not guarantee the accuracy or completeness, nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of goods, the merchantability of the goods or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage may be required. Whitlam assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of this data. No warranty against infringement of any patent, copyright or trademark is made or implied.